



*TYPICAL DIMENSION EXCEPT FOR A19, A21, & A22. (DIMENSION = (J - A) / 2)

**INDICATES CEMA STANDARD FLANGE.



BASE VALVE	A		B		C		D		E		F		G		H		J		K		L		Weight	
	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	Lbs.	Kg.
A06(150)	6	152	10	254	5	127	16	406	11	279	4 1/2	114	--	--	--	--	9	229	7/16	11	8	8	65	29
A08(200)	8	203	12	305	6	152	19	483	13	330	5 1/2	140	--	--	--	--	11	279	7/16	11	8	8	75	34
A10(250)	10	254	14	356	7	178	22	559	15	381	3 1/4	83	--	--	--	--	13	330	7/16	11	16	16	95	43
A12(300)	12	305	16	406	8	203	25	635	17	432	3 3/4	95	--	--	--	--	15	381	7/16	11	16	16	110	50
A13(325)**	13	330	17	432	8 1/2	216	26 1/2	673	18	457	5 1/4	133	--	--	5 1/8	130	15 1/2	394	7/16	11	12	12	130	59
A14(350)	14	356	18	457	9	229	28	711	19 1/4	489	4 1/4	108	--	--	--	--	17	432	7/16	11	16	16	150	68
A15(375)**	15	381	19	483	9 1/2	241	29 1/2	749	20 1/4	514	3 1/2	89	3 1/2	89	3 1/2	89	17 1/2	445	7/16	11	20	20	170	77
A16(400)	16	406	20	508	10	254	31	787	21 1/4	540	4 3/4	121	--	--	--	--	19	483	7/16	11	16	16	190	86
A17(425)**	17	432	21	533	10 1/2	267	32 1/2	826	22 1/4	565	4	102	4	102	3 3/4	95	19 1/2	495	7/16	11	20	20	210	95
A18(450)	18	457	22	559	11	279	34	864	23 1/4	591	5 1/4	133	--	--	--	--	21	533	7/16	11	16	16	230	104
A19(475)**	19	483	23	584	11 1/2	292	35 1/2	902	24 1/4	616	4 3/8	111	4 3/8	111	4 7/16	113	22	559	9/16	14	20	20	250	113
A20(500)	20	508	24	610	12	305	37	940	25 1/4	641	5 3/4	146	--	--	--	--	23	584	7/16	11	16	16	270	122
A21(525)**	21	533	25	635	12 1/2	318	38 1/2	978	26 1/4	667	4 3/4	121	4 3/4	121	4 7/8	124	24	610	9/16	14	20	20	290	132
A22(550)	22	559	26	660	13	330	40	1016	27 1/4	692	4 3/16	106	--	--	4 1/8	105	25 1/8	638	7/16	11	24	24	310	141
A24(600)	24	610	28	711	14	356	43	1092	32 1/8	816	4 1/2	114	--	--	--	--	27	686	7/16	11	24	24	395	179

*Information subject to change without notice | Above information is Vortex standard dimensional information | Contact us if your application needs a non-standard valve | Available specifications and modifications available at www.vortexvalves.com