



Model / Metric	Tube OD		A		B		C		D		E		F		G		H		J		K		M		N		WEIGHT	
	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	Lbs	Kg
T2-2(XX)Y / T50	2	51	30 1/2	775	5	127	5 7/8	149	7 3/4	197	7 1/4	184	3	76	4 1/4	108	2 1/2	64	4 3/4	121	2	51	6 1/4	159	5	127	80	36
T2.5-2(XX)Y / T65	2 1/2	64	35 1/4	895	6 1/2	165	7 3/4	197	9 7/8	251	8	203	4 1/8	105	5 1/4	133	3 1/2	89	5 1/4	133	2 1/2	64	8	203	6 5/8	168	90	41
T3-2(XX)Y / T75	3	76	34 1/8	867	6 1/2	165	7 3/4	197	9 7/8	251	8	203	2 7/8	73	4 1/8	105	3 1/2	89	6 1/4	159	3	76	8	203	6 5/8	168	95	43
T4-2(XX)Y / T100	4	102	43 5/8	1108	7 1/2	191	10 5/8	270	13 3/8	340	9 3/4	248	3 1/8	79	5 1/4	133	5	127	5 1/2	140	4	102	8 1/2	216	7 1/8	181	125	57
T5-2(XX)Y / T125	5	127	47 3/4	1213	9	229	13	330	15 3/8	391	11 3/4	298	3 3/4	95	5 1/8	130	6	152	6 3/4	171	5	127	9 3/4	248	9 1/8	232	145	66
T6-2(XX)Y / T150	6	152	60 1/8	1527	10 3/8	264	14 7/8	378	17 3/8	441	12 3/4	324	4	102	5 1/8	130	7	178	6 3/4	171	6	152	11 3/4	298	10 1/8	257	215	98
T8-2(XX)Y / T200	8	203	65 1/2	1664	12 1/2	318	21 1/2	546	23	584	16	406	3 7/8	98	9 1/4	235	10	254	7 5/8	194	8	203	13 1/8	333	13 1/8	333	265	120

*Information subject to change without notice | Above information is Vortex standard dimensional information | Contact us if your application needs a non-standard valve | Available specifications and modifications available at www.vortexvalves.com